


FRANKLIN
CLEANING TECHNOLOGY



RUST PENETRANT

**FOR PENETRATING RUST,
DRIVING OUT MOISTURE,
LUBRICATION, SURFACE
PROTECTION, FREEING
STICKY PARTS & MANY
MORE USES**

DANGER

EXTREMELY FLAMMABLE AEROSOL.
CONTENTS UNDER PRESSURE.
See back panel for additional safety information.

NET WT. 15 oz. (425 g)

RUST PENETRANT

RUST PENETRANT works quickly to free rusted bolts, nuts, pipe thread, locks, chains and other stuck parts. The special formulation penetrates tight crevices and threads to break the bonds that hold stuck parts together. It helps prevent rust and corrosion from re-forming and leaves behind a protective, lubricating layer. Safe for use on plastic, rubber and metals.

DIRECTIONS:

DIRECTIONS: Shake can well before use. Attach extension tube for tight areas or to focus on small areas (optional). Hold can 6-8 inches from application area. Spray until area is saturated and allow to soak for several minutes. Re-apply as needed.

DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Harmful in contact with skin. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Prevention

Keep away from heat / sparks / open flames / hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves / protective clothing.

Response

If swallowed: Call a poison center / doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice / attention. Call a poison center / doctor if you feel unwell. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents / container in accordance with local / regional / national / international regulations.


KEEP OUT OF REACH OF CHILDREN



Ingredients: Distillates (petroleum) hydrotreated Light (64742-47-8), Distillates (petroleum) dewaxed light paraffinic (64742-56-9), Isobutane (75-28-5), Propane (74-98-6), Highly-refined petroleum lubricant oils (64742-54-7), Ethylene glycol monobutyl ether (111-76-2).

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com



F762015-1116