

FLOOR CARE



Quasar®

Diamond Gloss Floor Finish

- **Durable, High-Solids Finish**
- **Labor Saving**
- **Superior Soil Resistance**



Quasar®

Diamond Gloss Floor Finish

Quasar® is a high solids, metal-crosslinked, water emulsion floor finish. Formulated for outstanding durability, **Quasar®** will outwear conventional finishes under the most demanding traffic and frequent scrubbing conditions. Excellent appearance levels may be achieved in a variety of maintenance programs. Use **Quasar®** on resilient surfaces and sealed wood.

Durable:

Exceptional resistance to heel marking, scuffing and repeated scrubbing with detergents means that **Quasar®** outwears conventional finishes. Both stripping and recoating cycles are extended, lowering the frequency of these costly procedures.

High Solids Formula:

Maximum labor productivity is assured as you build gloss quickly, with fewer coats.

Superior Soil Resistance:

The tough film of **Quasar®** minimizes soil penetration and surface abrasion even under extreme conditions. Autoscrubbing easily picks up dirt, immediately restoring the shine.

Versatility:

Maintain **Quasar®** using many recognized methods, spray buff, top coat or scrub/recoat.

USE INFORMATION:

Recommended on all types of resilient and non-resilient floors which include vinyl composition, rubber, asphalt, quarry, terrazzo and sealed wood floors. NOTE: Old and very porous floors should be sealed with a Franklin sealer prior to application of **Quasar®**.

PRODUCT SPECIFICATIONS:

pH.....	9.0 ± 0.3
Appearance.....	Off White Emulsion
Fragrance.....	Mild polymeric
Freezing Point.....	About 32°F
% Total Solids.....	30.8
% Non-Volatile Solids.....	25.0 ± 0.5
Boiling Point.....	212°F
Solubility in Water.....	Dispersible
Flash Point.....	None
Coverage.....	2500 to 3000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Styrene acrylic polymers.....	Mixture
Diethylene glycol monoethyl ether.....	111-90-0
Tri butoxyethyl phosphate.....	78-51-3
Polypropylene emulsion.....	Mixture
Oxidized Polypropylene wax emulsion.....	68441-17-8

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F1360SS-0318

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer or finish using an appropriate Franklin stripper and following label directions.
2. **APPLY** a thin, even coat of **Quasar®** using a clean finish mop.
3. **DRY:** Allow 20 to 30 minutes of drying time.
4. **APPLY** 2-3 coats for best results allowing for adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner. Follow label directions for correct dilution and proper cleaning procedure.
3. **BURNISH** the floor using a soft hair pad and high speed floor machine to remove black scuff marks, scuffs and scrapes.

PRODUCT AVAILABILITY:

F136022.....	4/1 Gal.
F136025.....	1/5 Cube
F136038.....	1/55 Drum