



# Aurora™

## ULTRA GLOSS URETHANE FORTIFIED FINISH

DATA TECH SHEET

**PRODUCT DESCRIPTION:**

**Aurora™** provides outstanding initial gloss and is urethane fortified for increased resistance to soil penetration, scuffing and black heel marks. **Aurora™** is an excellent choice for high speed and UHS maintenance programs.

**FEATURES:**

**Durable:**

Exceptional resistance to heel marking, scuffing and repeated scrubbing with detergents. Both stripping and recoating cycles are extended, lowering the frequency of these costly procedures.

**High Gloss Formula:**

The urethane fortified floor finish emulsion provides the highest level of gloss.

**Superior Soil Resistance:**

The tough film of **Aurora™** minimizes soil penetration and surface abrasion even under extreme conditions. Autoscrubbing easily picks up dirt, immediately restoring the shine.

**Versatility:**

**Aurora™** is an excellent choice for propane and high-speed burnishing programs and is formulated to be **VOC Compliant**.

**PRODUCT SPECIFICATIONS:**

pH	9.0 ± 0.3
Appearance	Off White Emulsion
Fragrance	Mild polymeric
Freezing Point	About 32°F
% Solids	20.0 ± 0.5
Boiling Point	212°F
Solubility in Water	Dispersible
Flash Point	None
Coverage	1800 to 2200 sq. ft. per gallon (may vary due to differences in porosity of the surface)

**INGREDIENTS:**

Water	7732-18-5
Styrene acrylic copolymer emulsion	Mixture
Diethylene glycol monoethyl ether	111-90-0
Tri-butoxyethyl phosphate	78-51-3
Polyethylene emulsion	Mixture

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 1	NFPA 0	NFPA 0
CONCENTRAR	HMIS 1	HMIS 0	HMIS 0
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico


# Aurora™ ULTRA GLOSS URETHANE FORTIFIED FINISH

# DIRECTIONS

## USE INFORMATION

Recommended on all types of resilient and non-resilient floors which include vinyl composition, rubber, asphalt, quarry, terrazzo and sealed wood floors. NOTE: Old and very porous floors should be sealed with a Franklin sealer prior to application of Aurora™.

### INITIAL APPLICATION



CAUTION 1. REMOVE 2. APPLY 3. WAIT 20 minutes 4. APPLY 5. BURNISH

### MAINTENANCE



1. DUST MOP 2. MOP 3. BURNISH

## INITIAL APPLICATION

1. **REMOVE** old sealer or finish using an appropriate Franklin stripper and following label directions.
2. **APPLY** a thin, even coat of Aurora™ using a clean finish mop.
3. **WAIT** 20 to 30 minutes of drying time.
4. **APPLY** 4 coats. For best results allow adequate drying time between each coat. Buffing is not necessary.
5. **BURNISH:** Recommended after last coat wait 24 hours.

## MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using Franklin UHS Combo Cleaner/Maintainer and following the label directions.
3. **BURNISH** the floor after cleaning with an ultra high speed or high speed machine using the appropriate pad. If the floor begins to look worn, an occasional scrub & recoat will decrease the need for frequent stripping.

## FIRST AID:

If in eyes or on skin, immediately flush with plenty of water. Get medical attention if irritation persists. If swallowed, get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

## HANDLING AND STORAGE:

**SUGGESTED STORAGE TEMPERATURE:** Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. **Protect from freezing.** Thoroughly rinse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

## PERSONAL PROTECTION:

**Respiratory Protection:** Not needed in normal use of this product.

**Ventilation:** Use with adequate ventilation.

**Eye Protection:** Safety glasses are recommended.

**Protective Gloves:** Protective gloves are optional.

**Other Protective Clothing or Equipment:** Wear clothing as necessary to prevent skin contact.

## TRANSPORTATION INFORMATION:

**U.S. DOT - Proper Shipping Name:** Not regulated by DOT.

**Marine Pollutant:** No.

**MSDS RETRIEVAL**  
Read MSDS before using this product

**800-848-4901**

**OBTENCIÓN DE HDSM**

Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY,  
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT  
CALL CHEMTREC DAY OR NIGHT

**800-424-9300**

PARA EMERGENCIAS QUÍMICA DERRAMES,  
ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE  
LLAMAR DE DÍA O DE NOCHE A CHEMTREC

**TECH HOTLINE**  
**800-810-4829**  
**LINEA DE TÉCNICA**