

Dimension™

LABOR REDUCING FLOOR FINISH

PRODUCT DESCRIPTION:

Dimension™ is an advanced technology floor coating specially formulated with our exclusive APT™ Polymer System. Dimension™ will provide exceptional durability, repairability and a beautiful wet look gloss, while reducing labor costs and burnishing frequencies up to 50%. Dimension™ allows facilities currently burnishing 5-7 times per week to reduce to 3-4 times per week when used according to directions with the recommended system components.

FEATURES: Durable:

Dimension™ is extremely resistant to abrasions such as scratching, scuffing and heel marking. Dimension™ will not capture and embed soils, which results in less time to clean, less chemical to use and less overall cost to maintain while enjoying a high maintenance look.

Easy to Apply:

Dimension™ has very little mop drag, providing opportunities for greater efficiency of application. Dimension™ can normally be recoated after 20 minutes.

Reduced Environmental Impact:

Because of reduced burnishing, exhaust fumes released into a facility when using propane equipment is reduced. Electric or battery powered burnishers use less energy too. By allowing reduced burnishing, Dimension™ reduces energy usage and helps provide a healthier, safer environment.

Cost Reducing:

Dimension™ can reduce burnishing, labor and associated costs by up to 50% in high maintenance programs while maintaining a wet gloss look.

PRODUCT SPECIFICATIONS:

pH	8.3 ± 0.4
Appearance	Off white emulsion
Freezing Point	About 32°F
% Total Solids	24.0
% Non-Volatile	18.5
Boiling Point	212°F
Flash Point	None
Coverage	up to 3000 sq. ft. per gallon
(may vary due to differences in porosity of the surface and application method used)	

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
NJ TSRN	100555-5009
Diethylene glycol ethyl ether	111-90-0
Tributoxyethyl phosphate	78-51-3
Dipropylene glycol methyl ether	34590-94-8

ECOLOGICAL INFORMATION:

- Contains No Phosphorus
- No Solvents

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 0	HMIS 0	NFPA 0
CONCENTRAR	HMIS 0	NFPA 0	HMIS 0
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

DATA SHEET

Dimension™


LABOR REDUCING FLOOR FINISH

DIRECTIONS

USE INFORMATION

Dimension is part of a complete floor care system made up of Franklin's OFFense Stripper, Super Gard Sealer and UHS Combo Cleaner/Maintainer. When used as directed this system will allow up to a 50% reduction of burnishing in high maintenance floor care programs while maintaining a wet look gloss. For use on vinyl composition, vinyl, asphalt, sealed concrete, terrazzo and sealed wood.

INITIAL APPLICATION



CAUTION



1. REMOVE



2. APPLY



3. DRY




4. APPLY



5. BURNISH


MAINTENANCE



1. DUST MOP



2. MOP



3. BURNISH

INITIAL APPLICATION

1. **REMOVE** old sealer/finish using **OFFense** stripper and following label directions. Before coating an old or porous floor use 2 coats of **Super Gard** to seal the floor.
2. **APPLY** a thin coat of **Dimension** using a clean **FULLPRO Finish Mop**.
3. **DRY**: Allow 20 minutes drying time.
4. **APPLY** a total of 4-6 thin coats allowing adequate drying time between each coat.
5. **BURNISH**: Optional - following last coat after minimum 1 hour dry time.

MAINTENANCE

1. **DUST MOP** the floor several times daily. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** daily using **UHS Combo Cleaner/Maintainer** and following the label directions.
3. **BURNISH** the floor 3-4 times per week with an ultra high speed machine (>2000 RPM) using an appropriate.

If the floor begins to look worn, a scrub & recoat after 6-8 weeks will decrease the need for frequent stripping.

WARNING

May cause mild eye and skin irritation.

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

KEEP OUT OF REACH OF CHILDREN

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use of this product.

Ventilation: Use with adequate ventilation

Eye Protection: Safety glasses are optional.

Protective Gloves: Safety gloves are optional.

Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION

INFORMATION:

U.S. DOT-Proper Shipping

Name: Not regulated by DOT.

Marine Pollutant: No