# FRANKLIN CLEANING TECHNOLOGY

### SAFETY DATA SHEET

#### 1. Identification

Product identifier TET Speed Spray Power Cleaner

Other means of identification

Product code F3790

Recommended use Multi-Use Cleaner
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Franklin Cleaning Technology

Address One Fuller Way

Great Bend, KS 67530

**United States** 

**Telephone** Customer Service (800) 810-4829

**E-mail** Not available.

Emergency phone number CHEMTREC (800) 424-9300

Emergency (620) 792-1711 24 hour Emergency (800) 424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Acute toxicity, oral Category 4

Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if swallowed. Causes severe skin burns and eye damage. Causes

serious eye damage. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or

vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse. In

case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

classified (HNOC)

Material name: TET Speed Spray Power Cleaner

1441 Version #: 02 Revision date: 05-11-2015 Issue date: 05-06-2015

59.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 59.5% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

#### 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name                            | Common name and synonyms | CAS number | %         |
|--|--------------------------|------------|-----------|
| 1-AMINO-2-PROPANOL                       |                          | 78-96-6    | 10 - < 20 |
| DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER   |                          | 34590-94-8 | 10 - < 20 |
| UNDECETH-7                               |                          | 34398-01-1 | 5 - < 10  |
| ALCOHOLS, C9-11,<br>ETHOXYLATED          |                          | 68439-46-3 | 1 - < 3   |
| Other components below reportable levels | 3                        |            | 60 - < 70 |

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

blindness could result.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

**Eye contact**Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** 

Ingestion

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

and precautions for firefighters
Fire-fighting

equipment/instructions

Specific methods

Specific methods

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: TET Speed Spray Power Cleaner

1441 Version #: 02 Revision date: 05-11-2015 Issue date: 05-06-2015

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

#### Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

| US. OSHA Table Z-1 Limits for Ai Components                | Type          | Value     |  |
|--|---------------|-----------|--|
| DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER<br>(CAS 34590-94-8) | PEL           | 600 mg/m3 |  |
| ,  |               | 100 ppm   |  |
| <b>US. ACGIH Threshold Limit Value</b>                     | es            |           |  |
| Components   | Туре          | Value     |  |
| DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER<br>(CAS 34590-94-8) | STEL          | 150 ppm   |  |
|  | TWA           | 100 ppm   |  |
| US. NIOSH: Pocket Guide to Cher                            | nical Hazards |           |  |
| Components   | Туре          | Value     |  |
| DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER<br>(CAS 34590-94-8) | STEL          | 900 mg/m3 |  |
|  |               | 150 ppm   |  |
|  | TWA           | 600 mg/m3 |  |
|  |               | 100 ppm   |  |

### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

#### **Exposure guidelines**

#### US - California OELs: Skin designation

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

#### US - Tennesse OELs: Skin designation

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

#### **US ACGIH Threshold Limit Values: Skin designation**

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

Material name: TET Speed Spray Power Cleaner

SDS US

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS Can be absorbed through the skin. 34590-94-8)

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.
Color Clear Purple
Odor Menthol like
Odor threshold Not available.

pH 10.5 - 11.5

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 212 °F (> 100 °C) estimated

Flash point 171.0 °F (77.2 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.18 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.18 lbs/gal estimated
Flammability class Combustible IIIA estimated

Percent volatile 86 % estimated

Pounds per gallon 8.13 - 8.23

Specific gravity 0.98 estimated

VOC (Weight %) 23.3 % estimated

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials. Strong oxidizing agents. Peroxides. Phenols.

Incompatible materials
Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

**Ingestion** Causes digestive tract burns. Harmful if swallowed.

**Inhalation** Prolonged inhalation may be harmful. May cause irritation to the respiratory system.

Skin contact Causes severe skin burns.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

cteristics .....

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product Species Test Results

TET Speed Spray Power Cleaner (CAS Mixture)

Acute Dermal

LD50 Rabbit 79.1667 g/kg estimated

Oral

LD50 Rabbit 504.008 g/kg estimated

Rat 45 ml/kg estimated

19.5775 g/kg estimated

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: TET Speed Spray Power Cleaner

1441 Version #: 02 Revision date: 05-11-2015 Issue date: 05-06-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not available.

**Chronic effects** Prolonged inhalation may be harmful.

#### 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

**Test Results Product** 

TET Speed Spray Power Cleaner (CAS Mixture)

Aquatic

Crustacea FC50 Daphnia 37.9696 mg/l, 48 hours estimated Fish LC50 Fish 48.706 mg/l, 96 hours estimated

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

1-AMINO-2-PROPANOL -0.96

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions** 

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

#### 14. Transport information

DOT

**UN** number Not available.

**UN** proper shipping name Transport hazard class(es) Consumer commodity

Class ORM-D

Subsidiary risk

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 156 156 Packaging non bulk None Packaging bulk

**IATA** 

UN3266 **UN** number

**UN** proper shipping name

Corrosive liquid, basic, inorganic, n.o.s., (Monoisopropanolamine)

Transport hazard class(es)

Class 8

Subsidiary risk Combustible Liquid

Material name: TET Speed Spray Power Cleaner

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Packing group III Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only Allowed.

Transport in bulk according to Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

the IBC Code

IATA



#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. All components are listed or exempted from listing on the U.S. EPA

TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

**US state regulations** 

US. Massachusetts RTK - Substance List

1-AMINO-2-PROPANOL (CAS 78-96-6)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

Material name: TET Speed Spray Power Cleaner

#### US. New Jersey Worker and Community Right-to-Know Act

1-AMINO-2-PROPANOL (CAS 78-96-6)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

#### US. Pennsylvania Worker and Community Right-to-Know Law

1-AMINO-2-PROPANOL (CAS 78-96-6)

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS 34590-94-8)

#### US. Rhode Island RTK

Not regulated.

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### 16. Other information, including date of preparation or last revision

 Issue date
 05-06-2015

 Revision date
 05-11-2015

Version # 02

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision Information** Composition / Information on Ingredients: Ingredients

Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Transport Information: Proper Shipping Name/Packing Group

Material name: TET Speed Spray Power Cleaner

1441 Version #: 02 Revision date: 05-11-2015 Issue date: 05-06-2015